Rack Station RS409+

Scalable 1U SATA NAS Server for Corporate Users



Key Features

- High Speed
 39+ MB/Sec RAID 5 Write
 55+ MB/Sec RAID 5 Read
- Hot-swappable HDD Design
- 2 Gigabit LAN Ports
- Windows + Mac + Linux
- Power Saving (28W~60W)

Shipped with Disk Station Manager 2.1 that provides:

- AJAX-Based Management Interface
- Windows ADS Support
- Business Mail Server
- Corporate Surveillance
- Schedule Power On/Off

And more...



Corporate IT Management

Synology Rack Station RS409+ supports various volume types, like basic, RAID 0/1/5/6, and RAID 5+Spare to fit users' needs. Advanced operations allow RAID expansion and RAID type changing to provide flexible management experience.

S.M.A.R.T. is a monitoring system for hard drives used to detect and report various attributes of reliability, helping to anticipate malfunctions.

The Link Aggregation feature provides share-loading and failover support for Synology Rack Station RS409+.

Affordable Scalability

When running out of the hard drive capacity on Synology Rack Station RS409+, users can expand more storage with Synology RX4. By attaching it to Synology Rack Station RS409+, the plug-n-use connectivity and eSATA 3.0 Gb/sec definition allow users to expand volume from Synology Rack Station RS409+. No firmware installation is needed.

Perfect Backup Solution

Synology Network Backup allows users to back up files from one to another Synology Disk Station or any rsynccompatible server, The Local Backup allows backups to external hard drives via USB or eSATA, both providing flexible scheduling options.

The Local Backup provides Synology Rack Station RS409+ with the ability to back up data to a shared folder or, to external USB or SATA hard drives.

Synology RX4 delivers a perfect backup solution for Synology Rack Station RS409+, too. By attaching it to Synology Rack Station RS409+, the plug-n-use connectivity and eSATA 3.0 Gb/sec definition allows users to create an independent volume on the RX4 as a good backup target. No firmware installation is needed.

Eco Friendly

Synology Disck Station is designed and developed perpetually with the concept of energy saving. Compared with average PC counterparts, Synology Rack Station RS409+ consumes a relatively low amount of power and hibernates when not in use. This not only helps to save energy but also extends the lifespan of the hard disk.

Additionally, all Synology products are produced with RoHS compliant parts and packed with recyclable packing materials. Synology recognizes its responsibility as a global citizen and is continually working to reduce the environmental impact of the products we create.

CONNECTIONS & BUTTONS



Fan	Power Swi	itch USB 2.0
	Q	
	<u> </u>	
A	l C Input	LAN COM Port

SYNOLOGY INC.

tional scale.

Synology Inc., founded in April 2000 by a duo experienced

Synology Inc., founded in April 2000 by a duo experienced in system designing and marketing, is a dedicated Network Attached Storage (NAS) products provider located in the Taipei city, Taiwan. With a staunch and united team organization, Synology creates and brings forth NAS servers of originality Synology Disk Station, for the global market. Under the breezy yet conscientious team work, Synology embodies the spirit of vitality, creativity, specialty, and versatility, implanting a new breath into the staid NAS business. With our sustained and cubatantial investment in research and development. Swnology

substantial investment in research and development, Synology is pursing the laurels of contemporary NAS industry on an

Synology NAS Servers are designed to fulfill its customers' need of security, performance, energy saving, and functionality on a broad range around the globe from prosumers to corporations. Moreover, to practice commitment made to its

widespread customers and to provide every possible means of satisfactory services, Synology is using its best endeavors to the establishment a fully developed customer support and service team. Having a vision beyond the visible, Synology Disk Station signifies –Value.

Copyright © 2009, Synology Inc. All rights reserved. Synology

Copyrigin & 2009, sprinody mic An ingine treastreat, synthogy, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice. Printed in Taiwan, R5409+-2009-ENU-REV002

http://www.synology.com 6F-2, No. 106, Chang An W. Rd., Taipei, Taiwa Tel: 886 2 2552 1814 Fax: 886 2 2552 1824

Technical Specifications

Hardware

- CPU: 1.06GHz, 64bit@DDR533, with floating point RAM Size: 1GB
- Internal HDD⁽¹⁾: 4X 3.5" SATA(II) External HDD Interface: 2X USB ports, 1X eSATA port Size: 44mm X 430.5mm X 457.5mm
- Weight: 7.1kg
- LAN: 2X Gigabit Fan: 3X (40mm X 40mm)

- Noise Level⁽²⁾: 36dB(A) Power Recovery AC Input Power Voltage: 100V to 240V Power Frequency: 50Hz to 60Hz, Single Phase
- Max HDD Support (Internal HDD): 2TB Max Supported IP Camera: 10 Operating Temperature: 5°C to 35°C (40°F
- to 95°F)
- Storage Temperature: -10°C to 70°C (15°F to 155°F) Relative Humidity: 5% to 95% RH
- Max Operating Altitude: 10,000 feet

Power Consumption⁽³ 60W (Access); 28W (Hibernation)

Certification

FCC Class B, CE Class B, BSMI Class B

- Networking Protocols
- CIFS
 AFP (3.1)
- FTP
- NFS Telnet/SSH

- Windows ADS Integration
 Supports up to Windows Server 2008
 Domain users login via Samba/AFP/FTP
- Synology Data Replicator 3 for Domain Users
- Security
- FTP over SSL/TLS (explicit)
 FTP Auto-Block
- Encrypted Network Backup
- Encrypted rsync
 HTTPS Connection

File System

- EXT3 FAT (External Disk Only)
- NTFS (External Disk Read Only)

- File Sharing

 Max User Account: 2,048
 Max Group: 256
- Max Shared Folder: 256 Max Concurrent Connections (SAMBA, FTP,
- AFP): 512

External Disk

RS409+

PC / Mac / Linux

THE HER

Networking

- Utilities Synology Assistant
- Synology Data Replicator 3 Synology Download Redirector Add Printer Wizard

Applications Surveillance Station 2

- Photo Station 3 File Station 2
- Audio Station
- Web Station
- PHP/MySQL
- Download Station 2 iTunes Server

Packages Mail Station

SqueezeCenter Weblizer

UPnP Multimedia Service Support

- Sony PS3, Microsoft Xbox360 Audio Format: AAC, FLAC, M4A, MP3, Ogg
- Vorbis, WAV, WMA, WMA VBR, WMA PRO WMA Lossless Video Format: ASF, AVI, DAT, DivX, MP4,
- MPEG I, MPEG2, MPEG4, VOB, WMV, XviD Image Format: BMP, JPG (jpe, jpeg), GIF, ICO, PNG, PSD, TIF (tiff), UFO
- Plavlist Format: WPL, M3U Subtitle: srt, psb, smi, ass, ssa, sub, idx, ifo

iTunes Server Support

 Audio Format: MP3, M4A, M4P, WAV⁽⁴⁾, AIF⁽⁴⁾ Plavlist Format: M3U, WPL

Audio Station Support

- USB Mode: (Audio) AAC, FLAC, M4A, MP3. Ogg Vorbis, WMA, WMA VBR (Playlist) M3U, WPL (Internet Radio) SHOUTcast, Radioio
- Streaming Mode: (Audio) MP3 (Playlist) M3U, WPL

 Photo Station 3 Support
 Video Format: ASF, AVI, MPEG1, MPEG4, WMV, XviD, DivX, FLV, DAT⁽⁵⁾, MP4⁽⁵⁾, MPEG2⁽⁵⁾, RM⁽⁵⁾, RMVB⁽⁵⁾, VOB⁽⁵⁾ Image Format: BMP, JPG (jpe, jpeg), GIF

- Management

 AJAX-based Management UI BitTorrent Port Range Setup
- BitTorrent DHT Support CIFS Recycle Bin
- Download Station Bandwidth control
- Download Station Port Range Setup Editable HTTP Error Page
- Email Alert Message
- Email Notification for New User Package Management

RS409+

Wireless Router

ΤV

3

- External HDD Hibernation
- Scheduled Power On/Off
- Firmware Upgrade
- FTP passive port range Hide-able Shared Folder

Synology Remote

IP Camera

Internal HDD Hibernation · Removable Default Shared Folder

- Ez-Internet
- PPPoE
- UPS Management (Over USB 2.0)
- User QuotaWeb-based Download Station

- RAID ManagementVolume Type: Basic, JBOD, RAID 0, RAID 1,
- RAID 5, RAID 5+Spare, RAID 6 RAID Change: Basic to RAID 1, RAID 1 to RAID 5, RAID 5 to RAID 5+Spare

- Expand with Larger Hard Drives: RAID 1, RAID 5, RAID 5+Spare, RAID 6
 Expand with More Hard Drive: RAID 5 from 3 to 4 HDDs

Backup Solutions

- Network Backup Local Backup
- · Desktop Backup (using Synology Data
- Replicator 3)
 3rd-Party Backup Support

Supported Protocols: LPR, CIFS, AppleTalk

English, Danish, Dutch, Norwegian, Swedish, German, French, Italian, Polish, Russian, Spanish, Korean, Traditional Chinese,

Simplified Chinese, Hungarian, Turkish,

Portuguese Brazil, Portuguese European

Rail Kit (Optional) L-type mounting brackets (Optional)

(1) Hard drive not included. (2) FAN only, Measured at 2300–6200RPM, varied among models. More details about dB(A) value, check http://www.quietnoise.com/facts.htm (3) Measured with 4 Seagater 5750G5 817350640NS hard drive. The figures could vary on different

environments. (4) The music can be streamed, but the metadata

(ex: title, album) may not be indexed on the iTunes. (5) User can click and download the file, but not

(b) Set Call Click and Colombia the life, But Hot
 (c) For Mac users, RS409+ supports PostScript USB printers only.

USB Printer

Supported Clients

Windows 2000 onward

· Mac OS X 10.3 onward

Printer Support⁽⁶⁾
Max Printer #: 2

Languages

Environment

RoHS Compliant

Package Content

RS409+ Main Unit

Installation CD

Welcome Note Assembling Kit

AC Power Cord

٨

USB Speakers

Digital Media Adapter

Stereo System

(1) Hard drive not included.

Linux