



Synology DiskStation DS410

4-bay All-in-1 NAS Server with Optimal Price/Performance Ratio for Home to Business Workgroup Users

Synology[®] DiskStation DS410 offers an affordable, high-performance and full-featured network attached storage solution that is specifically designed for home to business workgroup users who need to share and protect data cost-effectively, while increasing productivity with comprehensive business-oriented applications.

Highlights

- Optimal Price/Performance Ratio
- Power-saving with Only 56 Watts in Operation
- Wake on LAN/WAN
- Scheduled Power On/Off
- Supports both 3.5" and 2.5" Hard Drives
- Includes Feature-Rich Synology DiskStation Manager 2.3 (DSM 2.3)

Optimal Price/Performance Ratio

The Synology DS410 delivers an average 110 MB/sec reading speed under RAID 5 configuration in a Windows environment, and 54.9 MB/sec writing. The Synology DS410 provides a reliable solution for data sharing with an easy to use interface, and comprehensive businesses-oriented applications, including a complete backup solution making it one of the best values in 4-bay NAS devices available today.

Easy Setup and Management

For users who are limited on time and not familiar with configuring complicated routers, the Synology EZ-Internet Wizard simplifies the process of setting up access to the Synology DS410 from the Internet. The EZ-Internet Wizard steps through all of the settings including firewall settings, port-forwarding, PPPoE setup and DDNS registration.

Running on AJAX technology, the UI is intuitive and easy-to-use. Creating private shared folders for a large number of users is easy with the User Home feature because it minimizes the steps and time for the administrator to create private shared folders. The sub-folder privilege settings further extend the flexibility to allocate permissions for different workgroups.

Flexible RAID Management

The Synology Hybrid RAID (SHR) automatically builds an optimal RAID volume with data protection based on the hard drives installed, eliminating the need to have hard drives of identical size, while still offering a manual setup option for advanced users.

Complete Backup Solutions

The Synology DS410 offers a centralized backup target to consolidate fragmented and unstructured data across a network. PC Users can back up their data to the Synology DS410 using the free Synology Data Replicator software, while Mac OS X users enjoy native Apple® Time Machine integration. A web-based backup wizard is provided for backing up data in the Synology DS410 to another Synology DiskStation or any rsync server via an encrypted transmission, or to an external hard drive via USB or eSATA connection. In addition, backing up to the cloud using Amazon® S3 service is also supported.

Full-featured Business Applications

The Synology DS410 runs on the renowned system firmware, Synology DSM 2.3, offering comprehensive applications and features designed specifically for business workgroups. Comprehensive network protocol support assures seamless file sharing across Windows, Mac, and Linux platforms. Windows ADS integration allows the Synology DS410 to quickly and easily fit into an existing business network environment with no need to recreate user accounts on the Synology DS410.

Internet file access is simplified by the encrypted FTP server and the web-based file explorer, Synology File Station 3. HTTPS, firewall, and IP auto-block support ensure file sharing over the Internet is protected at a high security level.

Synology Web Station with support for PHP/MySQL web content allows hosting up to 30 websites on a Synology DS410. Synology Surveillance Station 4 offers a centralized interface to safeguard the office environments by deploying IP cameras. H.264 video format is supported to deliver high quality video. The Mail Station add-on turns a Synology DS410 into a mail server with only few steps of installation. The USB printer sharing capability minimizes businesses' cost by sharing printing resources throughout the office.

DSM 2.3 users are encouraged to develop and install third-party applications on the Synology DS410. Meanwhile, a list of third-party applications that were tested by Synology is available for users to install on the Synology DS410.

Energy Efficient Design

Synology DiskStations are designed and developed with energy efficiency in mind. Compared with the average PC counterparts, the Synology DS410 consumes only 56 watts in operation. The support of wake on LAN/WAN, scheduled power on/off and hard drive hibernation can further reduce power consumption and operation cost.

All Synology products are produced with RoHS compliant parts and packed with recyclable packing materials. Synology acknowledges the responsibility as a global citizen to continually work to reduce the environmental impact of every product produced.



CONNECTIONS & BUTTONS





SYNOLOGY INC.

individual users and families.

without notice. Printed in Taiwan, DS410-2010-ENU-REV001

Synology UK Ltd. Bluepoint House Davy Avenue, knowlhill Milton Keynes, Bucks MK5 8PB, UK Tel: +44 01908 673 709

http://www.synology.com Synology Inc. 3F-3, No. 106, Chang An W. Rd., Taipei, Taiwan Tel: +886 2 2552 1814 Fax: +886 2 2552 1824

Synology AMERICA Corp. 2899 152nd Ave NE, Redmond, WA 98052. USA Tel: +1 425 818 1587

Founded in 2000, Synology is a young and energetic company dedicated to developing high-performance, reliable, versatile, and environmentally-friendly Network Attached Storage (NAS) server products. Our goal is to deliver user-friendly solutions and solid customer service to satisfy the needs of businesses, home offices,

Copyright © 2010, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime,

USB 2.0 RESET Port eSATA Port

Technical Specifications

- Hardware CPU: 1.06GHz, with floating point RAM Size: 512 MB (64bit@DDR533) Internal HDD^{III}: 4X 3.5" SATA(II) or 4X 2.5" SATA/SSD External HDD Interface: 2X USB ports, 1X eSATA

- External HDD Interface: 2X USB ports, 1X eSATA port Size: 168mm X184mm X 230mm Weight: 2.23kg LAN: 1X (gabit Fan: 2X (80mm X 80mm) Noise Leve¹⁹: 23dB(A) Power Recovery AC Input Power Voltage: 100V to 240V Power Frequency: 50Hz to 60Hz, Single Phase Max Internal Capacity: 8TB (4X 2TB hard drives)⁽³⁾ Max Supported IP Camera It: 2¹⁰ Operating Temperature: 5°C to 3°C (40°F to 95°F) Storage Temperature: 5°C to 3°C (40°F to 95°F) Relative Humidity: 5% to 95% RH Max Operating Altitude: 10,000 feet

Power Consumption⁽⁵⁾ • 56W (Access); 20W (HDD Hibernation)

Certification • FCC Class, CE Class B, BSMI Class B

Networking Protocols

- CIFS AFP (3.1) FTP
- NFS
- Telnet/SSH

Windows ADS Domain Integration

- ADS Support Domain users login via Samba/AFP/FTP
- Synology Data Replicator 3 for Domain Users

- Security Firewall FTP over SSL/TLS (explicit) FTP Auto-Block Encrypted Network Backup Encrypted remot
- Encrypted rsync HTTPS Connection

File System

- EXT3
 FAT (External Disk Only)
- NTFS (External Disk Only)
- File Sharing
 Max User Account: 2,048
 Max Group: 256
 Max Shared Folder: 256
- Max Concurrent Connections (SAMBA, FTP, AEP): 256

Utilities

- Synology Assistant Synology Data Replicator 3 Synology Download Redirector
- Add printer wizard

Applications Surveillance Station

- Photo Station
- File Station
- Audio Station Web Station (PHP/MySQL) Download Station
- iTunes Server

Networking

- iPhone Applications DS photo
- DS audio DS cam

Packages Mail Station

phpMvAdmin SqueezeCenter Webalizer

DLNA/UPnP Media Server Support

- DLNA Certified Sony PS3, Microsoft Xbox360 Audio Format: AAC, FLAC, M4A, MP3, Ogg Vorbis, PCM, WAV, WMA, WMA VBR, WMA PRO, WMA Lossless Video Format: 3GP, 3G2, ASF, AVI, DAT, DivX,
- Video Format: 3GP, 3G2, ASF, AVI, DAT, DIXX, DVR-MS, ISO, M2T, M2TS, MAV, MKX, MPKA, MPEG1, MPEG2, MPEG4, MTS, MOV, QT, SWF, TP, TRP, TS, VOB, MMV, XviD Image Format: BMP, JPG (jpe, jpeg), GIF, ICO, PNG, PSD, TIF (tiff), UFO During Formate MPI. M311
- Playlist Format: WPL, M3U

iTunes Server Support • Audio Format^{i®}: MP3, M4A, M4P, WAV, AIF • Video Format: M4V, MOV, MP4 • Playlist Format: M3U, WPL

- Audio Station Support USB Mode: (Audio) AAC, FLAC, M4A, MP3, Ogg Vorbis, WMA, WMA VBR (Playlist) M3U, WPL (Internet Radio) SHOUTcast, Radioio Streaming Mode: (Audio) MP3 (Playlist) M3U, WPL

- Photo Station Support Video Format[®]: 3G2, 3GP, ASF, AVI, DAT, DivX, FLV, M4V, MOV, MP4, MPEG, MPG, QT, WMV, XviD, RM, RMVB, VOB

Image Format: BMP, JPG (jpe, jpeg), GIF

- Management AJAX-based Management UI Wake on LAN/WAN Sub-folder Privileges Setting User Home Applications privileges Setting BitTorgent Port Bange Setun

- BitTorrent Port Range Setup BitTorrent DHT Support

- BitTorrent DHT Support Changing Management UI Ports CIFS Recycle Bin Download Station Bandwidth control Download Station Port Range Setup Editable HTTP Error Page Email Alert Message Email Notification for New User Package Management External HDD Hibernation (eSATA, USB) Scheduled Power On/Off Firmware Upgrade
- Firmware Upgrade FTP passive port range Hide-able Shared Folder
- - Hide-able Shared Folder Internal HDD Hibernation Movable Shared Folder Removable Default Shared Folder System Temperature DDNS PPPoE Resource Monitor

- Resource Monitor SMS Notification
- SNMP
- UPS Management (Over USB 2.0)

External Disk

DS410

PC / Mac / Linux

User Quota Web-based Download Station

DS410

Wireless Router

PC / Mac / Linux

RAID/Storage Management
Volume Type: Basic, JBOD, RAID 0, RAID 1, RAID 5, RAID 5+Spare, RAID 6, RAID 10
Upgrade from Basic to RAID 1, from Basic to RAID 5, from RAID 1 to RAID 5, from RAID 5 to RAID

 Backup Solutions

 • Network Backup

 • Local Backup

 • Desktop Backup (using Synology Data Replicator 3 or Apple Time Machine backup application)

 • 3rd-Party Backup Support

5+Spare Expand RAID 1, RAID 5, RAID 5+Spare or RAID 6 with Larger Hard Drives Expand RAID 5 by Adding a Hard Drive On The Fly

iscs

Linux

onward)

• Max Printer #: 2

Environment

RoHS Compliant

Package Content

DS410 Main Unit

Installation CD Welcome Note

Assembling Kit AC Power Adapter AC Power Cord

2M RJ-45 LAN Cable

Supported Clients

Windows 2000 onward
Mac OS X 10.3 onward

Supported Browsers

Internet Explorer 7 and onward
Firefox 3 and onward

Supported Mobile Devices (Photo Station, File Station)

iPhone OS 2.2.1 and onward Windows Mobile 6.0 (IE Mobile or Opera 9.0

Symbian OS 9.1, S60 3rd Edition onward

Supported Protocols: LPR, CIFS, AppleTalk

Languages
English, German, French, Italian, Spanish, Danish, Norwegian, Swedish, Dutch, Russian, Japanese, Korean, Czech, Polish, Traditional Chinese, Simplified Chinese, Portuguese (Brazil),

Portuguese (European), Turkish, and Hungarian

(1) Hard drive not included. (2) FAN only. Measured at 2300~6200RPM, varied among models. More details about dB(A) value, check http://www.quietnoise.com/facts.htm

types. (4) 1 free license to install 1 IP camera. Additional licenses

(4) 1 free license to install 1 IP camera. Additional licenses can be purchased to expand the license quota. (5) Messured with 4 Seagate 750GB 513750640MS hard drive. The figures could vary on different environments. (6) The music can be streamed, but the metadata (ex: title, abum) may not be indexed on the Tiunes. (7) User can click and download the file, but not play it in Photo Station 3 as compressed Tash video. (8) For Mac users, the Synology D5410 supports PostScript USB printers only.

USB Printer

Windows ADS Server

IP Camera

(3) The actual capacity will differ according to volume

Safari 3 and onward (Mac)