

# SMCGS10P-Smart

**EZ Switch™ 10/100/1000 10-port Gigabit Web Smart PoE Switch Including 2 100/1000BASE-X SFP Slots**



## Product Overview

SMC Network's EZ Switch™ SMCGS10P-Smart is a new 10-port Gigabit Ethernet smart switch providing 8 Gigabit PoE ports and 2 100/1000BASE-X SFP slots. The switch supports a flexible web-based management interface as well as SNMP for both IPv4 and IPv6. The new SMCGS10P-Smart provides a range of feature-rich functions, including VLANs, Spanning Tree, link aggregation, multicasting, security, storm control, and QoS with 8 priority queues. Ideal for users looking to migrate from unmanaged to managed networks, this smart switch is easy to install and perfect for SMB and SOHO businesses.

## Key Features and Benefits

### Performance and Scalability

This entry-level managed switch provides 20 Gbps wire-speed switching performance across all 10 ports. This enables the switch to fully support existing high-performance PCs and laptops, which significantly improves application response times and the speed of large file transfers.

The two Gigabit Ethernet 100/1000BASE-X SFP slots provide uplink flexibility, offering extended fiber connections to the network backbone.

### Feature-Rich Functionality

VLAN features support flexible network partition and configuration, performance improvement, and cost savings.

IEEE 802.1Q-in-Q VLAN tags expand the VLAN space by double-tagging packets.

IGMP snooping prevents flooding of IP multicast traffic and limits bandwidth-intensive video traffic to only the subscribers.

Storm control monitors the amount of storm traffic that is sent every single second on an interface. It allows the administrator to specify how much storm traffic can be sent as a percentage of the total bandwidth of an interface.

### Continuous Availability

IEEE 802.1w Rapid Spanning Tree Protocol provides a loop-free network and redundant links to the core network with rapid convergence, ensuring faster recovery from failed links, and enhancing overall network stability and reliability.

IEEE 802.1s Multiple Spanning Tree Protocol runs STP per VLAN base (up to 8 instances), providing Layer 2 load sharing on redundant links.

IEEE 802.3ad Link Aggregation Control Protocol (LACP) increases bandwidth by automatically aggregating several physical links together as a logical trunk and providing load balancing and fault tolerance for uplink connections.

### Comprehensive QoS

Support for eight egress queues per port enable differentiated management of up to eight traffic types. Traffic is prioritized according to 802.1p, DSCP, IP precedence, and TCP/UDP port number, giving optimal performance to real-time applications such as voice and video. Asymmetric bidirectional rate-limiting, per port or per traffic class, preserves network bandwidth and allows maximum control of network resources.

### Enhanced Security

Port Security limits the total number of devices that can access a switch port based on MAC address, and protects against MAC flooding attacks.

IEEE 802.1X port-based or MAC-based access control ensures all users are authorized before being granted access to the network. User authentication is carried out using a standard-based RADIUS server, with support for dynamic VLAN assignment.

### Simple Management

An embedded user-friendly web interface helps users quickly and simply configure switches. SNMP v1/v2 is supported for management by a network management station. The switch supports management functions over both IPv4 and IPv6. Cable diagnostics identifies cable faults (such as short, open, etc.) and feeds back a distance to the fault. LLDP (Link Layer Discovery Protocol) enables administrators to monitor devices attached to switch ports.

### PoE Features

The SMCGS10P-Smart can provide up to 30 Watts of power to attached devices, such as VoIP phones, wireless access points, surveillance cameras, etc, all over existing Cat. 5 cables. The switch can deliver up to 30 Watts on 2 ports, 15.4 Watts on 4 ports, or 7.5 Watts on 8 ports. This eliminates the need for individual power sources for devices in the network, saving on costs for power cables and avoiding power outlet availability issues. If the power demand exceeds the switch's maximum power budget, ports can be prioritized to receive power.

## Features

### PHYSICAL PORTS

- 8 10/100/1000BASE-T RJ-45 PoE ports
- 2 Gigabit Ethernet SFP slots  
(SFP ports support dual speed 100/1000BASE-X)

### PERFORMANCE

- Switching Capability: 20 Gbps
- Packet Buffer Size: 1 MB
- MAC Address Table: 8K
- Flash: 8 MB

### L2 FEATURES

Auto-negotiation for port speed and duplex mode

Flow Control:

- IEEE 802.3x for full-duplex mode
- Back-Pressure for half-duplex mode

Spanning Tree Protocol:

- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- STP Auto Edge

VLANs:

- Supports 4K IEEE 802.1Q VLANs
- Port-based VLANs
- Voice VLAN
- Private VLAN
- Q-in-Q

Link Aggregation:

- Static Trunk
- IEEE 802.3ad Link Aggregation Control Protocol
- Trunk groups: 8 trunk links: Up to 8 ports

IGMP Snooping:

- IGMP snooping v1/v2/v3
- IGMP immediate leave
- Supports jumbo frames up to 9 KB

IEEE 802.3at Power over Ethernet (PoE)

- Maximum output power per port up to 30 W
- Maximum PoE power budget 75 W
- Data-pairs mode
- Maximum current: 1.7A
- Provides power on all 8 copper ports
- Power on/off command for each port
- LED indicators for power status per port

### QoS FEATURES

Priority Queues: 8 hardware queues per port  
Traffic classification based on IEEE 802.1p CoS, DSCP,  
Supports WRR, Strict scheduling, or hybrid mode  
Rate Limiting

- Ingress: Resolution 16 Kbps
- Egress: Resolution 16 Kbps

### SECURITY

Port security: static and dynamic  
Supports IEEE 802.1X port based and MAC-based  
EAPOL transparent  
MAC authentication  
Web authentication  
HTTPS/SSL  
SSH v1.5/v2.0  
MAC Filter/IP Filter  
DHCP Snooping

### MANAGEMENT

Switch Management:

- Web management
- SNMP v1/v2

Firmware and Configuration:

- Dual firmware/configuration upgrade/downgrade via TFTP/HTTP

Supports DHCP Client

Supports LLDP (802.1ab) and LLDP-MED

RMON (groups 1, 2, 3, and 9)

Port mirroring: one to one and many to one

Event log: local flash, syslog, remote server (RFC3164) and SMTP (RFC821)

SNTP (IPv4/IPv6)

Loop detection and prevention

UPnP

Cable diagnostics

### MANAGEMENT - CONTINUED

IPv6 management:

- IPv4/IPv6 dual protocol stack
- IPv6 address types: unicast/multicast
- IPv6 Ping/tracert
- ICMPv6 and ICMPv6 redirect
- IPv6 neighbor discovery
- IPv6 stateless auto config/manual config
- IPv6 Telnet/SNMP/HTTP/DHCP

### MECHANICAL

Dimensions (W x D x H)

- 33 x 20.4 x 4.3 cm (12.99 x 8.03 x 1.69 inches)

Weight: 2.2 kg (4.85 lbs)

LED Indicators: Port, Uplink, System, Diagnostic

### POWER SUPPLY

AC Power

- 100 to 240 V, 50-60 Hz, 0.7A

Power Supply

- Internal, auto-ranging transformer: 100 to 240 VAC, 50 to 60 Hz

Power Consumption

- 100 Watts for PoE Power and 20 Watts for System Power

Maximum Current

- 1.7A @ 100 VAC

### ELECTROMAGNETIC COMPATIBILITY

CE Mark

FCC Class A

EN 55022 (CISRP 22) Class A

EN 61000-3-2/3

### ENVIRONMENTAL SPECIFICATIONS

Temperature:

- 0°C to 50°C (standard operating)
- -40°C to 70°C (non-operating)

Humidity: 10% to 90% (non-condensing)

Vibration: IEC 68-2-36, IEC 68-2-6

Shock: IEC 68-2-29

Drop: IEC 68-2-32

### SAFETY

CSA (CSA 22.2 NO 60950-1 & UL 60950-1)

CB (IEC/EN60950-1)

### WARRANTY

Please check [www.smc.com](http://www.smc.com) for the warranty terms in your country.

## Contact

Worldwide Corporate and Sales Headquarters

No. 1 Creation Road III,

Science-based Industrial Park,

Hsinchu 30077, Taiwan, R.O.C.

Tel: +886 3 5770270 Fax: +886 3 5780764

Singapore

1 Coleman Street

#07-09, The Adelphi

Singapore 179803

Tel: 65-63387667 Fax: 65-63387767

Check [www.smc-asia.com](http://www.smc-asia.com) for your local country contact information.

Europe/Africa

C/Fructuós Gelabert 6-8 2º, 2ª,

Edificio Conata II,

08970 Sant Joan Despí

Barcelona - Spain

Phone: +34 93 477 4920

Check [www.smc.com](http://www.smc.com) for your local country contact information.

©2012 SMC Networks. EZ Switch™ is a trademark of SMC Networks.

Other trademarks or registered trademarks are the property of their respective owners. Information is subject to change without notice.

All rights reserved.