

WL-2000CAM

IR Wireless-G Multi-Profile IP Camera

T he WL-2000CAM is an IP camera designed for high-level video imaging experience that generates MPEG-4 and M-JPEG streaming. The infrared function offers superior low light performance with automatic night mode. It offers support for UPnP which makes seamless device connection and easy installation.





Full Function Wireless Camera

AirLive Wireless IP Cameras are designed for Home or Enterprise customers who demand performance with the latest technologies for mobility and functionality. It features simple plug-and-play installation and easy wireless operation that allows it to be placed anywhere effortlessly. The web-based configuration allows viewing the image from the Internet and various security functions such as video recording to a TFTP server. The 802.11g standard allows the camera to operate at 30 FPS and up to 640x480 VGA resolution. The 802.11g models add WPA support for even more secure data encryption.

Motion JPEG & MPEG-4 Compression Format

The WL-2000CAM is an advanced wireless IP camera with Motion JPEG and MPEG-4 capabilities. Using infrared illumination, Motion JPEG and MPEG-4 dual output stream allows for good compression performance with low bit rates and bandwidth requirements.

Versatile Application

This infrared IP camera comes equipped with many advanced features suitable for all types of applications. The camera supports FTP, TCP/IP, SMTP, HTTP and many other Internetrelated protocols for remote surveillance. Motion detection with up to three sensors enables optimal performance of video detection by capturing images and sending those images for e-mail notification. With built-in infrared LEDs



that allow viewing objects in the dark, the WL-2000CAM constantly delivers superior image detail in any environment.







2-Way Audio Communication

The WL-2000CAM supports 2-way audio with use of the built-in microphone and separate computer speakers which allows for real-time voice communication between the camera and PC.



Language Pack Feature

This camera also comes with upgradeable device language pack offering seven different languages for user-friendly operation. These languages include Chinese, German, Spanish, Japanese, and more.

Air Live	(www.airlive.com) WL-2000CAM IR Wireless-G Dual Stream IP Camera	Air Live	(www.airlive.com) WL-2000CAM IR Wireless-G Dual Stream IP Camera
🗂 Startseite	Neustart Neustart	🗂 Başa dön	Yeniden başlat Yeniden başlat
EINSTELLUNG	Werkseinstellung Werkseinstellung	AYARLAR	Fabrika ayarları Fabrika ayarları
 BASIC System 	Einstellungsdaten speichern Speichern	 BASİT Sistem 	Yedekleme ayar verileri Kaydet
Information	Einstellung zurücksetzen	Enformasyon	Ayarları geri yükle
Tag/Zeit	G Firmware Upgrade	Tarih/Saat	Yazılı güncelleme OK
Initialisieren		Başlat	Geri yükleme dil paketi I LM.1.6.16.01 tr.TR.lang
Kamera	Sprachpack hochladen LM 1.6.16.01_de-DE lang	Kamera	Geri yükleme dil paketi LLM.1.6.16.01_trTR.lang
Netzwerk	Sprache : Deutsch	▶ Ağ	Dil : Türkçe
Sicherheitsmodus		Güvenlik	
Erweitert		Gelişmiş	

View from Mobile Phone

The RSTP protocol feature allows 3G and 2.5G mobile phones to display captured images from the camera for live video surveillance from a remote location. With infrared technology that eliminates bit rate problems caused by poor night time performance, WL-2000CAM is the perfect answer to remotely monitoring your house while out traveling.





5F, No.96, Min-ChuanRd, Hsin-tien City, Taipei, Taiwan





Specifications

Models

- AirLive WL-2000CAM

Image Sensor - 1/4" Progressive CMOS Sensor

Zoom

- 10x Digital

Minimum Illumination - 0 Lux at F2.0 with Night-vision LEDs on

Video Compression

- Motion JPEG & MPEG-4

Max Resolution

- 640 x 480(VGA)

Frame Rate

- Motion JPEG: Up to 30 fps in all resolutions MPEG-4: Up to 30 fps in all resolutions

Video Streaming

- Simultaneous Motion JPEG and MPEG-4 Controllable frame rate and bandwidth 3GPP/ISMA RTSP compatible

Audio

- Two-way(full duplex) Built-in microphon

Alarm and Event Management

- Built-in multi-window motion detection Image upload over FTP, e-mail and HTTP Notification over TCP and e-mail

Connectors

- Ethernet RJ-45, audio line out

Processors and Memory

- ARM9 based 32-bit RISC CPU 32MB RAM, 4MB Flash

Operation System

- Linux 2.4

Power

- 5V DC,max 4.5 W

Operating Conditions

- 0-45 °C (32-113 °F) Humidity 20-80% RH(non-condensing)

Minimum System Requirements

- Pentium III CPU 500 MHz or higher, or equivalent AMD 128MB RAM Windows 98,ME,2000,XP,Vista Internet Explorer 6 or later

Supported Protocols

- TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, DNS, NTP, UPnP, RTSP, RTP, HTTP, TCP, UDP, 3GPP/ISMA RTSP

www.airlive.com



5F, No.96, Min-ChuanRd, Hsin-tien City, Taipei, Taiwan



Video Surveillance Software

- Professional surveillance application for viewing, recording and archiving up to 16 cameras

Approvals

- CE,FCC,RoHS

Ordering Information:

WL-2000CAM IR Wireless-G Multi-Profile IP Camera

Manufacturer **OvisLink Corp.**

5F, No.96, Min-ChuanRd, Hsin-tien City, Taipei, Taiwan

Dimensions

- 104 x 63 x 35mm**asas**